



SAFETY DATA SHEET

SECTION 1: CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

Product ID: NIT1001, NIT1002
Product Name: Nitro Brake Parts Cleaner
Revision Date: 20-Sep-21 **Supersedes Date:** 9-Oct-15
Version: 2
Distributor's Name: NitroLubricants, USA
Address: PO Box 204
Forest Lake, MN 55025
Emergency Phone: 800-535-5053
Information Phone: 855-587-7515
Product Recommended Use: Non-Chlorinated Degreaser

SECTION 2: HAZARDS IDENTIFICATION

Classification:

Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) - Category 3
Specific Target Organ Toxicity - Repeated Exposure - Category 2
Aspiration Hazard - Category 1
Skin Irritation - Category 2
Aerosol - Category 1
Eye Irritation - Category 2A
Reproductive Toxicity - Category 2

Pictograms:



Signal Word:

Danger

Hazardous Statements - Physical:

H222, H229 - Extremely flammable aerosol, pressurized container may burst if heated

Hazardous Statements - Health:

H336 - May cause drowsiness or dizziness
H373 - May cause damage to organs through prolonged or repeated exposure
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H361 - Suspected of damaging fertility or the unborn fetus

Precautionary Statements - General:

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P103 - Read label before use

Precautionary Statements - Prevention:

- P271 - Use only outdoors or in a well-ventilated area
- P260 - Do not breathe dust/fume/gas/mist/vapors/spray
- P264 - Wash thoroughly after handling
- P280 - Wear eye protection/face protection
- P202 - Do not handle until all safety precautions have been read and understood
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P211 - Do not spray on an open flame or other ignition source
- P251 - Do not pierce or burn, even after use.

Precautionary Statements - Responsive:

- P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P312 - Call a POISON CENTER or doctor/physician if you feel unwell
- P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- P331 - Do NOT induce vomiting
- P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
- P332 + P313 - If skin irritation occurs: Get medical advice/attention
- P362 + P364 - Take off contaminated clothing and wash before reuse
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P337 + P313 - If eye irritation persists: Get medical advice/attention
- P308 + P313 - If exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage:

- P403 + P405 - Store in a well-ventilated place. Store locked up
- P410 - Protect from sunlight
- P412 - Do not expose to temperatures exceeding 50°C/122°F.

Precautionary Statements - Disposal:

- P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<i>CAS #</i>	<i>Chemical Name</i>	<i>% by Weight</i>
0000067-64-1	Acetone	36% - 64%
0000108-88-3	Toluene	8% - 18%
0000074-98-6	Propane	8% - 18%
0001330-20-7	Xylene	7% - 16%
0000100-41-4	Ethylbenzene	1% - 2%

SECTION 4: FIRST AID MEASURES

Inhalation:

Take precautions to ensure your own safety (eg wear appropriate protective equipment). Remove source of exposure or move person to fresh air and keep comfortable for breathing. If exposed/feel unwell/concerned: call a POISON CENTER/doctor. Eliminate all ignition sources if safe to do so.

Eye Contact:

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do so. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: get medical advice/attention.

Skin Contact:

Take off immediately all contaminated clothing, shoes and leather goods (ex watchbands, belts). Gently blot or brush away excess product. Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. Call a POISON CENTER/doctor if you feel unwell. Store contaminated clothing under water and wash before reuse or discard. IF exposed or concerned: Get medical advice/attention

Ingestion:

Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. If vomiting occurs naturally, lie on your side, in the recovery position.

Never give anything by mouth to an unconscious or convulsing victim. Keep person warm and quiet.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Use water, fog, dry chemical or carbon dioxide. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

Unsuitable Extinguishing Media:

Water may be ineffective but can be used to cool containers exposed to heat or flame.

Specific Hazards in Case of Fire:

Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force.

Aerosol cans may rupture when heated. Heated cans may burst.

In fire, will decompose to carbon dioxide, carbon monoxide.

Fire-Fighting Procedures:

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions:

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Care should always be exercised in dust/mist areas.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedure:

Flammable/combustible material.

ELIMINATE all ignition sources (no smoking, flare, sparks or flames in immediate area). Stay upwind; keep out of low areas.

Immediately turn off or isolate any source of ignition. Keep unnecessary people away; isolate hazard area and deny entry. Do not touch or walk through spilled material. Clean up immediately. Use absorbent sweeping compound to soak up material and put into suitable container for proper disposal.

Recommended Equipment:

Positive pressure, full-face piece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

Personal Precautions:

Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Use explosion proof equipment. Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions:

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

SECTION 7: HANDLING AND STORAGE

General:

For industrial and institutional use only.
 For use by trained personnel only.
 Keep away from children.
 Wash hands after use.
 Do not get in eyes, on skin or on clothing.
 Do not breathe vapors or mists.
 Use good personal hygiene practices.
 Eating, drinking and smoking in work areas is prohibited.
 Remove contaminated clothing and protective equipment before entering eating areas.
 Eyewash stations and showers should be available in areas where this material is used and stored.

Ventilation Requirements:

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements:

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight and incompatibles. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not pressurize containers to empty them. Ground all sparks. Static electricity may accumulate and create a fire hazard. Store at temperatures below 120°F.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

Eye Protection:

Chemical goggles, safety glasses with side shields or vented/splash proof goggles. Contact lenses may absorb irritants. Particles may adhere to lenses and cause corneal damage.

Skin Protection:

Wear gloves, long sleeved shirt, long pants and other protective clothing as required to minimize skin contact. Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Chemical-resistant clothing is recommended to avoid prolonged contact. Avoid unnecessary skin contact.

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapors.

When spraying more than one half can continuously or more than one can consecutively, use NIOSH approved respirator.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m ³)	OSHA STEL (ppm)	OSHA STEL (mg/m ³)	OSHA-Tables Z1,2,3	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m ³)
Acetone	1000	2400			1			250	590
Ethylbenzene	100	435			1			100	435
Propane	1000	1800			1			1000	1800
Toluene	200(a)/300 ceiling	0.2	500 ppm/10minutes (a)		1, 2			100	375
Xylene	100	435			1			100	435
Chemical Name	NIOSH STEL (ppm)	NIOSH STEL (mg/m ³)	NIOSH Carcinogen	ACGIH TWA (ppm)	ACGIH TWA (mg/m ³)	ACGIH STEL (ppm)	ACGIH STEL (mg/m ³)		
Acetone				500	1188	750	1782		
Ethylbenzene	125	545		20					

Propane

See appendix F:
Minimal Oxygen
Content

Toluene

150

560

20

0.2

Xylene

150

655

100

434

150

651

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	6.23811 lb/gal
Density VOC	2.80715 lb/gal
% VOC	45.0%
VOC Actual	336.38068 g/l
VOC Regulatory	336.38068 g/l
VOC Actual	2.80715 lb/gal
VOC Regulatory	2.80715 lb/gal
Appearance	NA
Odor Threshold	NA
Odor Description	Solvent
pH	
Water Solubility	Not Soluble
Flammability	Flashpoint below 73°F
Flash Point Symbol	
Flash Point	0°F
Viscosity	NA
Lower Explosion Level	1
Upper Explosion Level	12.8
Vapor Pressure	NA
Vapor Density	Heavier than air
Melting Point	NA
Freezing Point	NA
Low Boiling Point	0°F
High Boiling Point	292°F
Decomposition Pt	0
Auto Ignition Temp	NA
Evaporation Rate	Slower than ether
VOC Composite Partial Pressure	NA

SECTION 10: STABILITY AND REACTIVITY

Stability:

Stable.

Conditions to Avoid:

High temperatures.

Incompatible Materials

None known.

Hazardous Reactions/Polymerization:

Will not occur.

Hazardous Decomposition Products:

In fire, will decompose to carbon dioxide, carbon monoxide.

SECTION 11: TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation:

Skin irritant.
Overexposure will cause defatting of skin.
Causes skin irritation.

Serious Eye Damage/Irritation:

Causes serious eye irritation.
Overexposure will cause redness and burning sensation.

Carcinogenicity:

Suspected of causing cancer.

Germ Cell Mutagenicity:

No data available.

Reproductive Toxicity:

Suspected of damaging fertility or the unborn fetus.

Respiratory/Skin Sensitization:

No data available.

Respiratory or Skin Sensitization:

Overexposure can cause irritation of respiratory tract, headache, dizziness, nausea and loss of coordination.

Specific Target Organ Toxicity - Single Exposure:

May cause drowsiness or dizziness.

Specific Target Organ Toxicity - Repeated Exposure:

May cause damage to organs.
May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard:

Aspiration hazard if swallowed. May be fatal if swallowed and enters airways.

Acute Toxicity:

0000067-64-1

Acetone

LC50 (male rat):	30000 ppm; 4-hour exposure (cited as 71000 mg/m ³ ; 4-hour exposure) (29)
LC50 (male mouse):	18600 ppm; 4-hour exposure (cited as 44000 mg/m ³ ; 4-hour exposure) (29)
LD50 (oral, female rat):	5800 mg/kg (24)
LD50 (oral, mature rat):	6700 mg/kg (cited as 8.5 mL/kg) (31)
LD50 (oral, newborn rat):	1750 mg/kg (cited as 2.2 mL/kg) (31)
LD50 (oral, mouse):	3000 mg/kg (32, unconfirmed)
LD50 (dermal, rabbit):	Greater than 16000 mg/kg (cited as 20 mL/kg) (30)

0000100-41-4

Ethylbenzene

LC50 (inhalation, rat):	4000 ppm; 4-hour exposure (3)
LD50 (oral, rat):	3.5 g/kg (1, 3, 5, 10)
LD50 (oral, rat):	4.72 g/kg (3, 5, 7, 8)
LD50 (dermal, rabbit):	17.8 g/kg (11)

0000108-88-3

Toluene

LC50 (rat):	8800 ppm; 4-hour exposure (2)
LC50 (rat):	6000 ppm; 6-hour exposure (3)
LD50 (oral, rat):	2600 to 7500 mg/kg (3, 5, 11, 17)
LD50 (oral, neonatal rat):	less than 870 mg/kg (3)
LD50 (dermal, rabbit):	12225 mg/kg (reported as 14.1 mL/kg) (1)

0001330-20-7

Xylene

LC50 (rat):	6350 ppm; 4-hour exposure (unspecified isomers and ethylbenzene) (1)
LC50 (rat):	6700 ppm; 4-hour exposure (65% m-xylene, 7.6% o-xylene, 7.8% p-xylene, 19.3% ethylbenzene) (2) Ethylbenzene (1)

LC50 (rat):	6700 ppm; 4-hour exposure (65% m-zylene, 7.6% o-zylene, 7.8% p-zylene, 19.3% ethylbenzene) (2)
LD50 (oral, rat):	5400 mg/kg (52% m-, 19% o-, 24% p-) (1)
LD50 (oral, female mouse):	5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17% ethylbenzene) (4)
LD50 (oral, male mouse):	5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17% ethylbenzene) (4)
LD50 (dermal, rabbit):	12180 mg/kg (m-zylene); greater than 1700 mg/kg (mixed zylenes - undefined composition) (3)
LD50 (oral, female mouse):	5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17% ethylbenzene) (4)
LD50 (oral, male mouse):	5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17% ethylbenzene) (4)
LD50 (dermal, rabbit):	12180 mg/kg (m-zylene); greater than 1700 mg/kg (mixed zylenes - undefined composition) (3)

Potential Health Effects - Miscellaneous

0000067-64-1 Acetone

The following medical conditions may be aggravated by exposure: lung disease, eye disorders, skin disorders. Overexposure may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, respiratory system, skin.

0000100-41-4 Ethylbenzene

As an IARC, NTP or OSHA carcinogen. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. Studies in laboratory animals have shown reproductive, embryotoxic and developmental effects. WARNING: This chemical is known to the State of California to cause cancer.

0000108-88-3 Toluene

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, respiratory system, skin. Can be absorbed through the skin in harmful amounts. Recurrent overexposure may result in liver and kidney injury. High airborne levels have produced irregular heartbeats in animals and occasional palpitations in humans. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown. WARNING: This chemical is known to the State of California to cause birth defects or other reproductive harm.

0001330-20-7 Xylene

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: bone marrow, cardiovascular system, central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. High exposures may produce irregular heartbeats. Canada classifies Xylene as a developmental toxin as high exposures to xylenes in some animal studies have been reported to cause health effects on the developing fetus/embryo. These effects were often at levels toxic to the adult animal. The significance of these effects to humans is not known. Repeated or prolonged skin contact may cause any of the following: irritation, dryness, cracking of the skin.

Chronic Exposure

0000100-41-4 Ethylbenzene

CARCINOGENIC EFFECTS: Ethylbenzene has been listed by IARC as Group 2B, Possibly Carcinogenic to Humans. TERATOGENIC EFFECTS: Ethylbenzene has been classified as POSSIBLE for humans.

0000108-88-3 Toluene

TERATOGENIC EFFECTS: Toluene has been classified as POSSIBLE for humans.

0001330-20-7 Xylene

Xylene in high concentrations has caused embryotoxic effects in laboratory animals. High exposure to Xylenes in some animal studies have been reported to cause health effects on the developing embryo/fetus.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity:

No data available.

Persistence and Degradability:

No data available.

Bio-Accumulative Potential:

No data available.

Mobility in Soil:

No data available.

Other Adverse Effects:

No data available.

Bio-Accumulative Potential:

0000067-64-1 Acetone

Does not bioaccumulate

Persistence and Degradability:

0000067-64-1 Acetone

91% readily biodegradable, Method: OECD Test Guideline 301B

SECTION 13: DISPOSAL CONSIDERATIONS

Water Disposal:

Under RCRA, it is the responsibility of the user of the product, to determine a time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14: TRANSPORT INFORMATION

U.S. DOT Information:

Consumer Commodity, ORM-D

IMDG Information:

Consumer Commodity, ORM-D

IATA Information:

Consumer Commodity, ORM-D

SECTION 15: REGULATORY INFORMATION


<i>CAS #</i>	<i>Chemical Name</i>	<i>% by Weight</i>	<i>Regulation List</i>
0000067-64-1	Acetone	36% - 64%	CERCLA, SARA312, TSCA, RCRA, ACGIH, OSHA
0000108-88-3	Toluene	8% - 18%	CERCLA, SARA312, SARA313, TSCA, RCRA, OH_TOX, ACGIH, CA_Prop65 - California Proposition 65, OSHA
0000074-98-6	Propane	8% - 18%	SARA312, TSCA, ACGIH, OSHA
0001330-20-7	Xylene	7% - 16%	CERCLA, SARA312, SARA313, TSCA, RCRA, ACGIH, OSHA
0000100-41-4	Ethylbenzene	1% - 2%	CERCLA, SARA312, SARA313, TSCA, ACGIH, CA_Prop65 - California Proposition 65, OSHA

SECTION 16: OTHER INFORMATION


Glossary:

ACGIH - American Conference of Governmental Industrial Hygienists; ANSI-American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC-Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA-Emergency Planning and Community Right-to-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC-Lethal Concentration; LD-Lethal Dose; NFPA-National Fire Protection Association; OEL-Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL-Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA-Self-Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ-Texas Commission on Environmental Quality; TLV-Threshold Limit Value; TSCA-Toxic Substances Control Act Public Law 94-469; TWA- Time-Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

HMIS



NFPA



Chronic:

DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.